

AS-INTERFACE-NEUHEITEN

MASI67 Passiv sichere Ausgänge

- 2 potenzialgetrennte Abschaltkreise
- 1 Ausgang je M12-Buchse mit Y-Verdrahtung
- 8 passiv sichere Ausgänge 1,6 A nach EN13849-1, Performance Level d
- Kurzschlussanzeige durch Status-LEDs an den Ausgängen

Art.-Nr. **56445** MASI67 D08 / 1,6 A AB K3 8xM12

MASI68 Passiv sichere Ausgänge

- sehr kompaktes Modul
- integrierte Busverteilerfunktion via M12
- 8 passiv sichere Ausgänge 0,5 A nach EN13849-1, Performance Level d
- Kurzschlussanzeige durch Status-LEDs an den Ausgängen

Art.-Nr. **56447** MASI68 D08 / 0,5 A AB E K3 4xM12



MASI68 Passivverteiler

- 2 x extern Power über 7/8" (je 8 A)
- 2 getrennte Abschaltkreise
- AS-Interface-Anschluss über M12-Stift
- Verteilung auf 3 x M12-Buchse

Art.-Nr. **56454** MASI68 Passivverteiler AS-i + 2x Pwr

MASI68 Digitale Ein-/Ausgänge

- hohe Schwing- und Schockbelastbarkeit
- sehr geringer Platzbedarf
- 2 digitale Eingänge M8, 200 mA Summenstrom
- 2 digitale Ausgänge M8 / 0,5 A (max. 1 A)

Art.-Nr. **56446** MASI68 DI2 DO2 / 0,5 A AB 4xM8



AS-INTERFACE PRODUCT NEWS

MASI67 Passive Safety Outputs

- 2 release circuits with potential separation
- 1 output per M12 female with Y wiring
- 8 passive safety outputs 1.6 A acc. to EN13849-1, Performance level d
- Short circuit indication with status LEDs at the outputs

Art. No. **56445** MASI67 D08 / 1.6 A AB K3 8xM12

MASI68 Passive Safety Outputs

- Very compact module
- Integrated bus distribution function with M12
- 8 passive safety outputs 0.5 A acc. to EN13849-1, Performance level d
- Short circuit indication with status LEDs at the outputs

Art. No. **56447** MASI68 D08 / 0.5 A AB E K3 4xM12



MASI68 Passive Distribution Box

- 2 x external power with 7/8" (8 A each)
- 2 separate release circuits
- AS-Interface connection with M12 pin
- Distribution to 3 x M12 female

Art. No. **56454** MASI68 Passive Distribution Box AS-I + 2x Pwr

MASI68 Digital Inputs/Outputs

- Very resistant to shock and vibration
- Requires minimum space
- 2 digital M8 inputs, 200 mA total current
- 2 digital M8 outputs / 0.5 A (max. 1 A)

Art. No. **56446** MASI68 DI2 DO2 / 0.5 A AB 4xM8

